Listing of Claims

- 1. (Currently Amended) A magnetic resonance imaging method for forming an image of an object, wherein
- a stationary magnetic field (G_0) and temporary magnetic fields having a position dependent field pattern $(G_1, G_2, G_3, ...)$ are applied,
- magnetic resonance signals are acquired by at least one receiver antenna,
- spins are excitated in a part of the object,
- MR signals are acquired during application of the position-dependent field patterns patterns (G₁, G₂,...)
- a magnetic resonance image is derived from the sampled magnetic resonance signals, whereas

the position dependent field patterns $(G_1, G_2,...)$ are substantially non-linear, the number N of total field patterns is larger than 3, and at least N – 1 field patterns are independently controllable in field strength.

- 2. (Original) A method as claimed in Claim 1, wherein the magnetic resonance signals are acquired in a sub-sampling fashion and the magnetic resonance image is derived from the sub-sampled magnetic resonance signals.
- 3. (Original) A method as claimed in Claim 2, wherein the magnetic resonance signals are sub-sampled by by means of an array of receiving antennae and the magnetic resonance image is derived from the sub-sampled magnetic resonance signals on the basis of the spatial sensitivity profiles of the array of receiving antennea.
- 4. (Currently Amended) A method as claimed in Claim 2, characterized-in that wherein fold-over artefacts are distinguished by continuity constraints of the object to be imaged.
- 5. (Currently Amended) A method as claimed in Claim 2, eharacterized in that wherein fold-over artefacts are distinguished and discarded by knowledge of the sparsity of the object to be imaged.

- 6. (Currently Amended) A magnetic resonance imaging apparatus for obtaining an MR image from a plurality of signals comprising:
- means (10, 12) for applying a stationary magnetic field and temporary, substantially non-linear magnetic fields having a position dependent field pattern,
- at least one receiving antenna (13, 15) for acquiring magnetic resonance signals, during application of position-dependent field patterns $(G_1, G_2,...)$,
- means (13) for excitation of spins in a part of the object,
- means (25) for deriving a magnetic resonance image from the sampled magnetic resonance signals,

wherein the magnetic field means are arranged to obtain substantially non-linear magnetic fields, whereas the number N of total field patterns is larger than 3, and at least N-1 field patterns are independently controllable in field strength.

- 7. (Original) An apparatus as claimed in Claim 6, wherein means are provided for acquiring the magnetic resonance signals in a sub-sampling fashion and means for deriving the magnetic resonance image from the sub-sampled magnetic resonance signals.
- 8. (Original) An apparatus as claimed in Claim 7, wherein an array of receiver antennae and means for determining the sensitivity profiles of the receiver antennae are provided.
- 9. (Currently Amended) A computer program product stored on a computer usable medium for forming an image by means of the magnetic resonance method, comprising a computer readable program means for causing the computer to control the execution of:
- applying a stationary magnetic field and temporary magnetic fields having a position dependent field pattern, whereas the magnetic fields are substantially non-linear and the number N of total field patterns is larger than 3,
- acquiring magnetic resonance signals by at least one receiver antenna,
- exciting spins in a part of the object,
- acquiring MR signals during application of position-dependent field patterns $(G_1, G_2,...)$,

- deriving a magnetic resonance image is from the sampled magnetic resonance signals,

controlling at least N-1 field patterns independently in their field strength.

10. (Original) A computer program product as claimed in Claim 9, additionally acquiring the magnetic resonance signals in a sub-sampling fashion and deriving the magnetic resonance image from the sub-sampled magnetic resonance signals.